FSF-25V328E -25℃ Medical Deep Freezer

FSF-25V328E (328L Medical Deep Freezer) is widely used in hospitals and laboratories. This is for placing and preserving storage such as drugs, vaccines, blood, enzymes, hormones, stem cells, extracted RNA and gene libraries and important biological and chemical reagents.

Features

- Fast pull down:Better cooling performance.
- Coil evaporator:Better temperature uniformity.
- Inner-door design:5 individual inner door.
- Universal castor wheels:Proven heavy-duty castors with brake.
- Lockable doors:Standard lock with keys.
- High-quality steel materials:Antibacterial and corrosion resistant.
- Precise temp. Control:Temp. control accurate to 0.1℃.
- 5 types of alarm:Audible and visual alarms.
- Variable space:Height adjustable shelves.
- Eco-friendly:CFC-free refrigerant and energy-saving.



Structure

- High-precision control system
- Magnetic block
- Inner door with built in handle
- Lock & Key
- High-precision probe
- Hight adjustable shelf
- Heavy duty hinge
- Castor with brake
- Sensor erro alarm
- High/low temp. Alarm
- Power failure alarm
- Door ajar alarm
- Thermostat failure alarm
- Coil evaporator cooling system
- 5 independent inner doors

Optional Accessories

- USB interface
- Data logger

Technical Parameter

Performance		Refrigeration System		Alarms	
Cooling method	Direct Cooling	Refrigerant	R290	High/low temperature	Y
Defrost	Manual	Temp. controller	Microprocessor	Power failure	Y
Shelf/drawer	Shelves/4	Sensor	NTC	Sensor error	Y
Temperature range	-10℃~-25℃	Display	Digital display	Controller failure	Y
Ambient temperature	10~32℃	External material	SPCC sprayed steel	Door ajar	Y
Noise(db)	46	Internal material	SPCC sprayed steel	Power failure backup(for controller)	8 hours
Access port QTY/Dia.	1/25mm	Compressor QTY	1		
Capacity(L/cu.ft)	328/11.6				

Electrical Data		Dimensions		Other	
Voltage frequency	220V 50/60Hz ; 110V/60Hz	Package size(W*D*H)(mm)	750*750*2020	Inner door Qty	5
Power(W)	218W	Exterior size(W*D*H)(mm)	673*676*1886	Remote alarm port	Y
Current(A)	1.59A	Interior size(W*D*H)(mm)	508*455*1393	USB port	Optional
Power consumption	1.71 kWh/24h	NW./GW.(kg)	104/123.5	Data logger	Optional