Class N Semi-automatic Autoclave





Features

- Two fixed sterilization programs, 121°C/1.1Bar and 134°C/2.1Bar.
- High precision temperature control within 0.1°C.
- Pressure safety lock,only allows the door to open when the pressure is 0.
- Safety door lock,only allows the cycle to start when the door is properly locked.
- Automatically discharge of water and steam after cycle over.
- SUS304 Stainless steel sterilizing chamber.

Technical Parameter

Model	FSF-18E	FSF-23E
Sterilizing Chamber Volume	18L Φ250x350mm	23L Φ250x450mm
Working Pressure	1.1Bar@121℃,2.1Bar@134℃	
Working Temperature	121℃/134℃	
Temperature Accuracy	0.1℃	
Max.Pressure	2.3Bar	
Time Range	30-60min @121℃/10-20min @10-20min	
Display	LED	
USB Interface	No	
Standard Function	Safety valve, Pressure lock system,Pressure & temperature overload protection	
Standard Tray No.	2	2
Tray Size (mm)	285x190x18	285x190x18
Material of Tray	Aluminum	Aluminum
Exterial Size (mm)	490x455x600	490x455x690
Packing Size (mm)	560x510x675	560x510x765
N.W./G.W. (kg)	47/50	49/52