Vertical Pulse Vacuum Steam Sterilizer

Used to medical and health undertakings,scientific research,agriculture and other units,medical equipment,dressing glassware,solution medium disinfection and sterilization.



Production Introduces

- Fully stainless steel structure.
- Hand wheel type of quick-open door structure.
- LCD display of working status,touch type key.
- Door safety lock system.
- Self-inflating type seal.
- Over temperature&over pressure auto-protection.
- Safe protection of water lacking.
- Automatically shut off with beep reminding after sterilization.
- With two stainless steel sterilizing baskets.
- A high efficiency filter is added to the exhaust.

Technical Parameter

Model	FSF-50HV	FSF-75HV	FSF-100HV
Chamber Volume	50L Φ340*550mm	75L Φ400*600mm	100L Φ400*650mm
Design Pressure	0.3MPa		
Design Temperature	150℃		
Max.Working Pressure	0.25MPa		
Max.Working Temperature	138℃		
Heat Average	≤±1℃		
Timer Range	0-99min		
Power	(3.2+1.6)kW/AC220V.50 HZ	(3.2+1.8)kW/AC220V.50 HZ	(3.2+1.9)kW/AC220V.50 HZ
Overall Dimension (mm)	660*460*1160	700*520*1250	820*560*1270
Transport Dimension (mm)	740*550*1270	87780*600*1410	950*680*1430
G.W/N.W(kg)	137/114	168/142	190/168